



专利产品 Patented Product





3D View













Recommended P.C.B layout (Top View)
Tolerance ±0.05



Recommended Module case cutout size
建议机壳匹配的开孔尺寸



Mating View


Notes:

1. Material Specification
   1-1.Housing: High Temperature Thermoplastic, UL94 V-0,
   1-2.Contact: High Conductivity Copper Alloy,
   1-3.Screw-Hole: Copper Alloy.
2. Plating Specification
   Contact: Gold plating on Contact area, Matte Tin 80μ" min. on Tails, and 100μ" min. Nickel overall,
3. Electrical performance
   3-1. Voltage Rating: 125v DC max./power blade;
   3-2. Current Rating: 20A max./Per pair power blade;
   3-3. LLCR: initial 0.5mΩ max.,
   finished 1.0mΩ maximum change.(per pair power blade);
   3-4. Dielectric Withstanding Voltage: 500v AC (RMS) for 60S ;
   3-5. Insulation Resistance: 1000 MΩ min/Power blade.
4. Mechanical Performance:
   4-1. Insertion Force: 9.8N (1.0kgf) max./Per Pair;
   4-2. Withdrawal Force: 3.5~8.5N (0.35~0.86kgf)/Per Pair;
   4-3. Durability Life: 3,000 cycles.
5. IR Reflow:
   The peak temperature on board shall be maintained for 10 seconds at 260±5°c.
6. Waterproof Level ≥IPX6 in the mated connector module state.
7. Operating Temperature Range: -40~125°c(without loss function).
8. All parts RoHS and Reach compliant.


THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED		PART NO.	Prolanv®
.X± 0.30	.X°± 3°	PDC6810C0001	
.XX± 0.20	.X°± 2°	APPROVED BY: Henry	TITLE: EN20A series | Power Female R/A DIP Type. 12PW
.XXX± 0.10	.XX°± 1°		
CUSTOMER DRAWING		CHECKED BY: Poplar	DWG NO.: PDC68-10
SIZE: A4	UNITS: mm[only]	DRAWN BY: Bing	SHEET: 1 / 2 · SCALE: 1:1 · REV: A2


Copyright Shenzhen Prolanv Inc. www.prolanv.com




30 Pcs/Tray











Total: 2x8Layers





Notes:

1. Q'ty:30 Pcs/Tray, 2x8 Layers=480 Pcs/Carton.
2. Tray Pallet size: 340*170mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION	GENERAL TOLERANCES UNLESS SPECIFIED: .X± 0.30, X.°± 3°; .XX± 0.20, .X°± 2°; .XXX± 0.10, .XX°± 1°	PART NO. PDC6810C0001	Prolanv®
		APPROVED BY Henry	TITLE EN20A series | Power Female R/A DIP Type. 12PW Packaging
	CUSTOMER DRAWING	CHECKED BY Poplar	DWG NO. P-PDC68-10
	SIZE: A4; UNITS: mm[only]	DRAWN BY Bing	SHEET: 2 / 2; SCALE: NA; REV: A2

Copyright Shenzhen **Prolanv** Inc. www.prolanv.com