


专利产品 Patented Product WaterProof 防水




3D View




Recommended P.C.B layout (Top View)
Tolerance ±0.05





Mating View






Recommended Module case cutout size
建议机壳匹配的开孔尺寸







Notes:

1. Material Specification
   1-1.Housing: High Temperature Thermoplastic, UL94 V-0,
   1-2.Contact: High Conductivity Copper Alloy,
   1-3.Screw-Hole: Copper Alloy.
2. Plating Specification
   Contact: Gold plating on Contact area, Matte Tin 80μ" min. on Tails, and 100μ" min. Nickel overall,
3. Electrical performance
   3-1. Voltage Rating: 125v DC max./power blade;
   3-2. Current Rating: 20A max./Per pair power blade;
   3-3. LLCR: initial 0.5mΩ max.,
   finished 1.0mΩ maximum change.(per pair power blade);
   3-4. Dielectric Withstanding Voltage: 500v AC (RMS) for 60S ;
   3-5. Insulation Resistance: 1000 MΩ min/Power blade.
4. Mechanical Performance:
   4-1. Insertion Force: 9.8N (1.0kgf) max./Per Pair;
   4-2. Withdrawal Force: 3.5~8.5N (0.35~0.86kgf)/Per Pair;
   4-3. Durability Life: 3,000 cycles.
5. IR Reflow:
   The peak temperature on board shall be maintained for 10 seconds at 260±5°c.
6. Waterproof Level ⩾IPX6 in the mated connector module state.
7. Operating Temperature Range: -40~125°c(without loss function).
8. All parts RoHS and Reach compliant.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED			
.X±	0.30	X.°±	3°
.XX±	0.20	.X°±	2°
.XXX±	0.10	.XX°±	1°

CUSTOMER DRAWING	
SIZE	UNITS
A4	mm[only]


PART NO.	PDC7010C0001
APPROVED BY	Henry
CHECKED BY	Poplar
DRAWN BY	Bing

Prolanv®


TITLE	EN20A series | Power Female R/A DIP Type. 14PW
DWG NO.	PDC70-10


SHEET	SCALE	REV
1 / 2	1:1	A2

Copyright Shenzhen Prolanv Inc. www.prolanv.com




25 Pcs/Tray





Total: 2x8Layers



Notes:

1. Q'ty:25 Pcs/Tray, 2x8 Layers=400Pcs/Carton.
2. Tray Pallet size: 340*170mm.
3. Carton size: 350*350*155mm.

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF Prolanv AND SHALL NOT BE COPIED OR USED WITHOUT Prolanv PERMISSION

GENERAL TOLERANCES UNLESS SPECIFIED		PART NO.	Prolanv®
X± 0.30	X.°± 3°	PDC7010C0001	
.XX± 0.20	.X°± 2°	APPROVED BY: Henry	TITLE: EN20A series | Power Female R/A DIP Type. 14PW Packaging
.XXX± 0.10	.XX°± 1°		
CUSTOMER DRAWING		CHECKED BY: Poplar	DWG NO.: P-PDC70-10
SIZE: A4	UNITS: mm[only]	DRAWN BY: Bing	SHEET: 2 / 2 | SCALE: NA | REV: A2

Copyright Shenzhen **Prolanv** Inc. www.prolanv.com